



GENERAL NOTES

- COORDINATE EXACT LOCATION OF EACH LIGHTING FIXTURE WITH CABLE TRAY LAYOUTS AND AIR DUCT LAYOUTS.
- FIXTURES SHALL BE LOCATED AT THE SAME ELEVATION IN EACH ROOM, UON.
- FOR LIGHTING PANEL SCHEDULES SEE DWG E9.21.34
- FOR LIGHTING FIXTURE SCHEDULES SEE DWG E9.30.01
- PROVIDE 2" RIGID GALVANIZED STEEL SLEEVES FOR ALL CONCRETE CEILING AND WALL CONDUIT PENETRATIONS. LOCATE WALL PENETRATIONS IN THE BASEMENT 12" BELOW CEILING. SEE DETAILS AS NOTED.
- ALL CONDUITS RUN IN THE CEILING AREA IN THE BASEMENT SHALL BE MINIMUM OF 8'-6" ABOVE THE FINISHED FLOOR.

SHEET KEYNOTES

- N001 ALL CONDUITS, CONDUIT FITTINGS AND J-BOXES IN THIS ROOM SHALL BE NON CORROSIVE EPOXY COATED GALVANIZED RIGID STEEL. WIRING DEVICES (SWITCHES, ETC.) SHALL BE ENCLOSED IN EPOXY COATED STEEL OR STAINLESS STEEL ENCLOSURES.
- N002 SEE DWGS. E8.10.32 & E8.10.33 FOR STAIRS NO.1, 2, 5, 6, 7 & 8 SECTIONS

0.1 0.6 1 2.5 4 5 6

0.5

D

NOTE 6 (TYP)

11

MTD 12'-0" AFF (TYP)

N001

B4 (TYP.)

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

SHEET KEYNOTES

- N001 ALL CONDUITS, CONDUIT FITTINGS AND J-BOXES IN THIS ROOM SHALL BE NON CORROSIVE EPOXY COATED GALVANIZED RIGID STEEL. WIRING DEVICES (SWITCHES, ETC.) SHALL BE ENCLOSED IN EPOXY COATED STEEL OR STAINLESS STEEL ENCLOSURES.
- N002 SEE DWGS. E8.10.32 & E8.10.33 FOR STAIRS NO.1, 2, 5, 6, 7 & 8 SECTIONS

0.1 0.6 1 2.5 4 5 6

0.5

D

NOTE 6 (TYP)

11

MTD 12'-0" AFF (TYP)

N001

B4 (TYP.)

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

SHEET KEYNOTES

- N001 ALL CONDUITS, CONDUIT FITTINGS AND J-BOXES IN THIS ROOM SHALL BE NON CORROSIVE EPOXY COATED GALVANIZED RIGID STEEL. WIRING DEVICES (SWITCHES, ETC.) SHALL BE ENCLOSED IN EPOXY COATED STEEL OR STAINLESS STEEL ENCLOSURES.
- N002 SEE DWGS. E8.10.32 & E8.10.33 FOR STAIRS NO.1, 2, 5, 6, 7 & 8 SECTIONS

0.1 0.6 1 2.5 4 5 6

0.5

D

NOTE 6 (TYP)

11

MTD 12'-0" AFF (TYP)

N001

B4 (TYP.)

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

SHEET KEYNOTES

- N001 ALL CONDUITS, CONDUIT FITTINGS AND J-BOXES IN THIS ROOM SHALL BE NON CORROSIVE EPOXY COATED GALVANIZED RIGID STEEL. WIRING DEVICES (SWITCHES, ETC.) SHALL BE ENCLOSED IN EPOXY COATED STEEL OR STAINLESS STEEL ENCLOSURES.
- N002 SEE DWGS. E8.10.32 & E8.10.33 FOR STAIRS NO.1, 2, 5, 6, 7 & 8 SECTIONS

0.1 0.6 1 2.5 4 5 6

0.5

D

NOTE 6 (TYP)

11

MTD 12'-0" AFF (TYP)

N001

B4 (TYP.)

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

6

SHEET KEYNOTES

- N001 ALL CONDUITS, CONDUIT FITTINGS